

High Voltage Probe P6040A



Characteristic

- 1000:1 attenuation
- BNC interface compatible with all major oscilloscope brands
- It can be connected to a multimeter with the PL-10

Model	P6040A
Bandwidth(-3dB)	DC-100MHz
Attenuation Ratio	1000:1
DC+AC peak	40kV/5Min
AC RMS	28kV/5Min
DC V Accuracy	≤3%(0~40kV)
AC V Accuracy	≤3% at 1kHz
Input impedance	400MΩ
Input Capacitor	2pF
Adjustable Capacitance Range	10pF~35pF
The pulse voltage	<20kVp-p
Max.Loading Current	100μA
Rise Time	3.5ns
Noise	>60dB at 1kHz; >50dB at 1MHz
Operation temp	-10~55°C
Operation humidity	≤85%RH
Dimension(Φ×L)	Φ87×410mm
Weight	480g

● ACCESSORIES



Accessory Kit



Adjustment Tool



Alligator Clip



High Voltage Insulation Head

GUANGZHOU PINTECH CO.,LIMITED

Web:www.pintech.com.cn

Tel:86-20-82510899

E-mail:sales@pintech.com.cn

Main Products

Optical Isolated Voltage Probe, Differential probe, Oscilloscope probe, High voltage probe, High frequency current probe, Current probe, Digital high voltage meter, High voltage amplifier, Power amplifier, ESD generator, Function generator, Oscilloscope, Spectrum analyzer, multimeter, High voltage power supply, AC power supply, DC power supply and Power equipment instrument.